



- Doors meet AWS Section 9 Premium quality standards
- Panels are glass
- Stiles and Rails are Structural Composite Lumber (SCL) or Stave Lumber with 1/42" veneer and matching hardwood edge
- Factory machined to exact requirements for hardware, including pre-drilled pilot holes for hinges and faceplates
- FSC certified, subject to availability; Chain of Custody Code SW-COC-001518
- Limited 5-year warranty for interior use

#### FACTORY FINISH

- Doors are available with AWS System 2 - pre-catalyzed lacquer factory finish.
- VT color choices are available or custom color matching by submitting a physical sample (minimum 3"x5").
- All VT factory-finished doors have sealed top and bottom rails.

#### STICKING OPTIONS

- Reference *Artistry Collection Sticking*
- Custom sticking available

#### DIMENSIONS (Maximum and Minimum)

Door Height	Door Width	Door Thickness	Stile Width	Top Rail Width
12' maximum 2' minimum	5'-6" maximum 1' minimum	3-3/8" maximum 1" minimum	12" maximum 5" minimum	12" maximum 3" minimum
Bottom Rail Width	Rail Length	Panel Height	Panel Width	Bar/Muntin Width
18" maximum 3" minimum	5' maximum 6" minimum	11'-6" maximum 6" minimum	5' maximum 6" minimum	15/16" maximum 1/2" minimum
Bar/Muntin Thickness				
1-3/4" maximum 1-3/8" minimum				