



- Doors meet AWS Section 9 Premium quality standards
- Panels are MDF with 1/42" veneer on each side
- Stiles and Rails are Structural Composite Lumber (SCL) with 1/42" veneer and matching hardwood edge
- Factory machined to exact requirements for hardware, including pre-drilled pilot holes for hinges and faceplates
- FSC certified, subject to availability; Chain of Custody Code SW-COC-001518
- Limited 5-year warranty for interior use

FACTORY FINISH

- Doors are available with AWS System 2 - pre-catalyzed lacquer factory finish.
- VT color choices are available or custom color matching by submitting a physical sample (minimum 3"x5").
- All VT factory-finished doors have sealed top and bottom rails.

STICKING OPTIONS

- Reference *Artistry Sticking Options* for availability up to 3/4"
- Dadoed construction available for flat panels up to 1-1/4", with or without sticking
- Custom sticking available

DIMENSIONS (Maximum and Minimum)

Door Height	Door Width	Door Thickness	Stile Width	Mullion Width
12' maximum 2' minimum	5'-6" maximum 1' minimum	3-3/8" maximum 1" minimum	12" maximum 5" minimum	12" maximum 3" minimum
Top Rail Width	Cross/Lock Width	Bottom Rail Width	Rail Length	Panel Height
12" maximum 3" minimum	12" maximum 3" minimum	18" maximum 3" minimum	5' maximum 6" minimum	11'-6" maximum 6" minimum
Panel Width	Flat Panel Thickness			
5' maximum 6" minimum	1-1/4" standard* 1/4" minimum			

*Maximum – 1/2" less than maximum door thickness.