



- Doors meet WDMA I.S. 6-A Custom Grade quality standards
- Stiles and Rails are Structural Composite Lumber (SCL) with 1/24" veneer and matching hardwood edge
- Factory machined to exact requirements for hardware, including
- pre-drilled pilot holes for hinges and faceplates
- Composite woods and adhesives contain no added urea formaldehyde
- Limited 5-year warranty for interior use

FACTORY FINISH

- Doors are available with WDMA TR-6 catalyzed polyurethane factory finish.
- VT color choices are available or custom color matching by submitting a physical sample (minimum 3"x5").
- All VT factory-finished doors have sealed top and bottom rails.

STICKING OPTIONS

- Reference *Heritage Sticking Options – 3000 Series*
- Custom sticking available

DIMENSIONS (Maximum and Minimum)

Door Height	Door Width	Door Thickness	Stile Width	Top Rail Width
10'-0" maximum 1'-2" minimum	4'-0" maximum 1'-0" minimum	2-1/4" maximum 1-3/8" minimum	10" maximum 3" minimum	10" maximum 3" minimum
Bottom Rail Width	Glass Height	Glass Width	Bar/Muntin Width	
10" maximum 3" minimum	9'-6" maximum 6" maximum	3'-6" maximum 6" minimum	15/16" maximum 1/2" minimum	